
# KASHIMA 620 **0961**

# SKU 1174002







# PRODUCT SPECIFICATION

#### **GENERAL**

FINISH: Polished Chrome MAIN MATERIAL: Metal - Mild Steel

H: 45mm W: 620mm D: 190mm **DIMENSIONS:** 

INSTALLATION ORIENTATION: Wall Mount - Horizontal

Not Applicable **CUT OUT HOLE: RECESS DEPTH:** Not Applicable

FIRE RATING: Not Applicable

CABLE LENGTH: Not Applicable **GROSS WEIGHT:** 1.863 (kg) CLASS: CE (Class II) IP RATING: IP44

**BATHROOM ZONE:** Zone 2, 3 VOLTAGE: Mains 230V

PRODUCT F MARK:

MACADAM ELIPSE:

Suitable for mounting on flammable materials

## LAMP

LIGHT SOURCE: MAXIMUM WATTAGE: 14W

MAXIMUM LAMP LENGTH: Not Applicable

LAMP INCLUDED? Yes **LUMINOUS FLUX:** 542.4 (lm) COLOUR TEMP: Lamp Dependent CRI: Lamp Dependent

R9: -8.3

Not Applicable UGR: Not Applicable **BEAM ANGLE:** Not Applicable TILT ADJUSTMENT ANGLE: Not Applicable **ROTATION ADJUSTMENT ANGLE:** Not Applicable AVERAGE LIFESPAN:

L70:

12,000 (Hrs) Not Applicable

Yes (Integral)

### **ELECTRICAL**

SWITCHED: Nο DIMMABLE: No

DIMMING METHOD: Not Applicable **DRIVER OUTPUT CURRENT:** Not Applicable DRIVER OUTPUT VOLTAGE: Not Applicable

SUPPLY FREQUENCY: 50/60 (Hz) DRIVER/BALLAST VOLTAGE: 220-240 (V) DRIVER AVERAGE LIFESPAN: Not Applicable EFFICACY: 33.9 (lm/W) DRIVER/BALLAST INCLUDED?

# ADDITIONAL INFORMATION





This product is not suitable for use with a PIR motion detector.



**BOX QUANTITY X8** 

