

PRODUCT SPECIFICATION

GENERAL

FINISH:	Polished Chrome	CABLE LENGTH:	Not applicable
MAIN MATERIAL:	Metal - Mild Steel	GROSS WEIGHT:	5.26 (kg)
DIMENSIONS:	H: 510mm W: 80mm D: 80mm	CLASS:	CE (Class I)
INSTALLATION ORIENTATION:	Not Applicable	IP RATING:	IP44
CUT OUT HOLE:	Not Applicable	BATHROOM ZONE:	Zone 2, 3
RECESS DEPTH:	Not Applicable	VOLTAGE:	Mains 230 (V)
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE:	2G11	MACADAM ELIPSE:	Not Applicable
MAXIMUM WATTAGE:	36W	UGR:	Not Applicable
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	Not Applicable
LAMP INCLUDED?	No	TILT ADJUSTMENT ANGLE:	Not Applicable
LUMINOUS FLUX:	1462 (lm)	ROTATION ADJUSTMENT ANGLE:	Not Applicable
COLOUR TEMP:	Lamp Dependent	AVERAGE LIFESPAN:	20,000 (hrs)
CRI:	80	L70:	Not Applicable
R9:	-28.3		


ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	50/60 (Hz)
DIMMABLE:	No	DRIVER/BALLAST VOLTAGE:	220-240 (V)
DIMMING METHOD:	Not Applicable	DRIVER AVERAGE LIFESPAN:	Not Applicable
DRIVER OUTPUT CURRENT:	Not Applicable	EFFICACY:	36.33 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER INCLUDED?	Yes (Integral)

ADDITIONAL INFORMATION



This product is not suitable for use with a PIR motion detector.



BOX QUANTITY X6

PRODUCT ELEVATIONS

