



## PRODUCT SPECIFICATION

### GENERAL

<b>FINISH:</b>	Polished Chrome	<b>CABLE LENGTH:</b>	Not Applicable
<b>MAIN MATERIAL:</b>	Metal - Mild Steel	<b>GROSS WEIGHT:</b>	0.9 (kg)
<b>DIMENSIONS:</b>	H: 225mm W: 150mm D: 280mm	<b>CLASS:</b>	CE (Class II)
<b>INSTALLATION ORIENTATION:</b>	Wall Mount - Vertical	<b>IP RATING:</b>	IP44
<b>CUT OUT HOLE:</b>	Not Applicable	<b>BATHROOM ZONE:</b>	Zone 2, 3
<b>RECESS DEPTH:</b>	Not Applicable	<b>VOLTAGE:</b>	Mains 230 (V)
<b>FIRE RATING:</b>	Not Applicable	<b>PRODUCT F MARK:</b>	Suitable for mounting on flammable materials

### LAMP

<b>LIGHT SOURCE:</b>	G9	<b>MACADAM ELIPSE:</b>	Not Applicable
<b>MAXIMUM WATTAGE:</b>	40W Max	<b>UGR:</b>	Not Applicable
<b>MAXIMUM LAMP LENGTH:</b>	To Be Advised	<b>BEAM ANGLE:</b>	Not Applicable
<b>LAMP INCLUDED?</b>	No	<b>TILT ADJUSTMENT ANGLE:</b>	Not Applicable
<b>LUMINOUS FLUX:</b>	Lamp Dependent	<b>ROTATION ADJUSTMENT ANGLE:</b>	180 (Degrees)
<b>COLOUR TEMP:</b>	Lamp Dependent	<b>AVERAGE LIFESPAN:</b>	Lamp Dependent
<b>CRI:</b>	Lamp Dependent	<b>L70:</b>	Not Applicable
<b>R9:</b>	Lamp Dependent		


### ELECTRICAL

<b>SWITCHED:</b>	No	<b>SUPPLY FREQUENCY:</b>	Not Applicable
<b>DIMMABLE:</b>	Yes	<b>DRIVER / BALLAST VOLTAGE:</b>	Not Applicable
<b>DIMMING METHOD:</b>	Lamp Dependent	<b>DRIVER AVERAGE LIFESPAN:</b>	Not Applicable
<b>DRIVER OUTPUT CURRENT:</b>	Not Applicable	<b>EFFICACY:</b>	Lamp Dependent
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER / BALLAST INCLUDED?</b>	Not Applicable

## ADDITIONAL INFORMATION



SHADE INCLUDED



BOX QUANTITY X12

# PRODUCT ELEVATIONS

---

