



PRODUCT SPECIFICATION

GENERAL

| | | | |
|----------------------------------|---------------------------|------------------------|--|
| FINISH: | Polished Chrome | CABLE LENGTH: | Not Applicable |
| MAIN MATERIAL: | Metal - Mild Steel | GROSS WEIGHT: | 0.833 (kg) |
| DIMENSIONS: | H: 225mm W: 85mm D: 135mm | CLASS: | CE (Class I) |
| INSTALLATION ORIENTATION: | Wall Mount - Vertical | IP RATING: | IP20 |
| CUT OUT HOLE: | Not Applicable | BATHROOM ZONE: | Zone 3 |
| RECESS DEPTH: | Not Applicable | VOLTAGE: | Mains 230 (V) |
| FIRE RATING: | Not Applicable | PRODUCT F MARK: | Suitable for mounting on flammable materials |


LAMP

| | | | |
|-----------------------------|----------------|-----------------------------------|----------------|
| LIGHT SOURCE: | G9 | MACADAM ELIPSE: | Not Applicable |
| MAXIMUM WATTAGE: | 60W Max | UGR: | Not Applicable |
| MAXIMUM LAMP LENGTH: | To Be Advised | BEAM ANGLE: | Not Applicable |
| LAMP INCLUDED? | No | TILT ADJUSTMENT ANGLE: | Not Applicable |
| LUMINOUS FLUX: | Lamp Dependent | ROTATION ADJUSTMENT ANGLE: | Not Applicable |
| COLOUR TEMP: | Lamp Dependent | AVERAGE LIFESPAN: | Lamp Dependent |
| CRI: | Lamp Dependent | L70: | Not Applicable |
| R9: | Lamp Dependent | | |

ELECTRICAL

| | | | |
|-------------------------------|----------------|-----------------------------------|----------------|
| SWITCHED: | No | SUPPLY FREQUENCY: | Not Applicable |
| DIMMABLE: | Yes | DRIVER / BALLAST VOLTAGE: | Not Applicable |
| DIMMING METHOD: | Lamp Dependent | DRIVER AVERAGE LIFESPAN: | Not Applicable |
| DRIVER OUTPUT CURRENT: | Not Applicable | EFFICACY: | Lamp Dependent |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER / BALLAST INCLUDED? | Not Applicable |

ADDITIONAL INFORMATION



BOX QUANTITY X6

PRODUCT ELEVATIONS

