



PRODUCT SPECIFICATION

GENERAL

| | | | |
|----------------------------------|-------------------------|------------------------|--|
| FINISH: | Plaster | CABLE LENGTH: | Not Applicable |
| MAIN MATERIAL: | Plaster | GROSS WEIGHT: | 0.75 (kg) |
| DIMENSIONS: | H:100mm W: 70mm D:100mm | CLASS: | CE (Class I) |
| INSTALLATION ORIENTATION: | Wall Mount - Vertical | IP RATING: | IP20 |
| CUT OUT HOLE: | Not Applicable | BATHROOM ZONE: | Zone 3 |
| RECESS DEPTH: | Not Applicable | VOLTAGE: | Mains 230V |
| FIRE RATING: | Not Applicable | PRODUCT F MARK: | Suitable for mounting on flammable materials |


LAMP

| | | | |
|-----------------------------|----------------|-----------------------------------|----------------|
| LIGHT SOURCE: | High-Power LED | MACADAM ELIPSE: | To Be Advised |
| MAXIMUM WATTAGE: | 1 x 3W | UGR: | Not Applicable |
| MAXIMUM LAMP LENGTH: | Not Applicable | BEAM ANGLE: | Not Applicable |
| LAMP INCLUDED? | Yes (Integral) | TILT ADJUSTMENT ANGLE: | Not Applicable |
| LUMINOUS FLUX: | 104.3 (lm) | ROTATION ADJUSTMENT ANGLE: | Not Applicable |
| COLOUR TEMP: | 3000 (K) | AVERAGE LIFESPAN: | 60,500 (hrs) |
| CRI: | 80 | L70: | To Be Advised |
| R9: | -8 | | |

ELECTRICAL

| | | | |
|-------------------------------|----------------|-----------------------------------|----------------|
| SWITCHED: | No | SUPPLY FREQUENCY: | 50/60 (Hz) |
| DIMMABLE: | No | DRIVER / BALLAST VOLTAGE: | 220-240 (V) |
| DIMMING METHOD: | Not Applicable | DRIVER AVERAGE LIFESPAN: | 60,000 (Hrs) |
| DRIVER OUTPUT CURRENT: | 700 (mA) | EFFICACY: | 26.2 (lm/W) |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER / BALLAST INCLUDED? | Yes (Integral) |

ADDITIONAL INFORMATION



BOX QUANTITY X12

PRODUCT ELEVATIONS

