

PRODUCT SPECIFICATION

GENERAL

FINISH:	White	CABLE LENGTH:	Not Applicable
MAIN MATERIAL:	Metal - Mild Steel	GROSS WEIGHT:	To Be Advised
DIMENSIONS:	H:450mm W:150mm D:155mm	CLASS:	CE (Class I)
INSTALLATION ORIENTATION:	Wall Mount - Vertical/Horizontal	IP RATING:	IP20
CUT OUT HOLE:	Not Applicable	BATHROOM ZONE:	Zone 3
RECESS DEPTH:	Not Applicable	VOLTAGE:	Mains 230v
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Suitable for mounting on flammable materials

MAIN LAMP

LIGHT SOURCE:	LED Strip	R9:	To Be Advised
MAXIMUM WATTAGE:	11.5 (W)	MACADAM ELIPSE:	To Be Advised
MAXIMUM LAMP LENGTH:	Not Applicable	UGR:	Not Applicable
LAMP INCLUDED?	Yes (Integral)	BEAM ANGLE:	Not Applicable
LUMINOUS FLUX:	427 (lm)	AVERAGE LIFESPAN:	Not Applicable
COLOUR TEMP:	2700 (K)	L70:	To Be Advised
CRI:	80		

ADDITIONAL LAMP


LIGHT SOURCE:	High Power LED	MACADAM ELIPSE:	3-Step
MAXIMUM WATTAGE:	3W	UGR:	To Be Advised
LAMP INCLUDED?	Yes (Integral)	BEAM ANGLE:	To Be Advised
LUMINOUS FLUX:	123 (lm)	TILT ADJUSTMENT ANGLE:	90 (Degrees)
COLOUR TEMP:	2700 (K)	ROTATION ADJUSTMENT ANGLE:	330 (Degrees)
CRI:	80	AVERAGE LIFESPAN:	To Be Advised
R9:	To Be Advised	L70:	To Be Advised

ELECTRICAL


SWITCHED:	Yes	DRIVER / BALLAST VOLTAGE:	100-240 (V)
DIMMABLE:	No	DRIVER AVERAGE LIFESPAN:	30,000 (Hrs)
DIMMING METHOD:	Not Applicable	MAIN LAMP EFFICACY:	28.92 (lm/W)
DRIVER OUTPUT CURRENT:	700 (mA)	ADDITIONAL LAMP EFFICACY:	30.32 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER / BALLAST INCLUDED?	Yes (Integral)
SUPPLY FREQUENCY:	50/60 (Hz)		

PRODUCT ELEVATIONS


TOP




FRONT




SIDE



BACK



ADDITIONAL INFORMATION



BOX QUANTITY X4