MASHIKO 300 SQUARE LED II **7942 SKU** 1121040

astro



PRODUCT SPECIFICATION

GENERAL

FINISH: Polished Chrome

MAIN MATERIAL: Metal - Stainless Steel

DIMENSIONS: H: 300mm W: 300mm D: 87mm

INSTALLATION ORIENTATION: Ceiling Mount
CUT OUT HOLE: Not Applicable
RECESS DEPTH: Not Applicable
FIRE RATING: Not Applicable

CABLE LENGTH:

ROSS WEIGHT:

CLASS:

CE (Class II)

IP RATING:

BATHROOM ZONE:

VOLTAGE:

PRODUCT F MARK:

Not applicable

2.8 (Kg)

CE (Class II)

IP44

Zone 2, 3

Voltage:

Mains 230 (V)

Suitable for mo

Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE: LED Module MAXIMUM WATTAGE: 16W MAXIMUM LAMP LENGTH: Not Applicable LAMP INCLUDED? Yes (Integral) **LUMINOUS FLUX:** 930.88 (lm) COLOUR TEMP: 2700 (K) CRI: 80 R9: 5.5

MACADAM ELIPSE: 6 MacAdam

UGR: Not Applicable
BEAM ANGLE: Not Applicable
TILT ADJUSTMENT ANGLE: Not Applicable
ROTATION ADJUSTMENT ANGLE: Not Applicable
AVERAGE LIFESPAN: 20,000 (Hrs)
L70: To Be Advised

ELECTRICAL


SWITCHED: SUPPLY FREQUENCY: 50/60 (Hz) Not Applicable DIMMABLE: No DRIVER/BALLAST VOLTAGE: 220-240 (V) DIMMING METHOD: Not Applicable DRIVER AVERAGE LIFESPAN: 20,000 (Hrs) **DRIVER OUTPUT CURRENT:** Not Applicable EFFICACY: 57.07 (Im/W) DRIVER OUTPUT VOLTAGE: DRIVER INCLUDED? Not Applicable Yes (Integral)


ADDITIONAL INFORMATION


BOX

BOX QUANTITY X4

CE







T: +44 (0) 1279 427001 F: +44 (0) 1279 427002 sales@astrolighting.com www.astrolighting.com