

OSCA LED ROUND 7996

SKU 1252022

astro



PRODUCT SPECIFICATION

GENERAL

| | | | |
|----------------------------------|-------------------|------------------------|----------------------------------------------|
| FINISH: | Matt White | CABLE LENGTH: | Not Applicable |
| MAIN MATERIAL: | Metal - Aluminium | GROSS WEIGHT: | 0.378 (Kg) |
| DIMENSIONS: | D: 80mm DIA: 80mm | CLASS: | CE (Class I) |
| INSTALLATION ORIENTATION: | Ceiling Mount | IP RATING: | IP20 |
| CUT OUT HOLE: | Not Applicable | BATHROOM ZONE: | Zone 3 |
| RECESS DEPTH: | Not Applicable | VOLTAGE: | Mains 230V |
| FIRE RATING: | Not Applicable | PRODUCT F MARK: | Suitable for mounting on flammable materials |

LAMP

| | | | |
|-----------------------------|----------------|-----------------------------------|----------------|
| LIGHT SOURCE: | LED Module | MACADAM ELLIPSE: | 3-Step |
| MAXIMUM WATTAGE: | 7.7W | UGR: | Not Applicable |
| MAXIMUM LAMP LENGTH: | Not Applicable | BEAM ANGLE: | 50 (Degrees) |
| LAMP INCLUDED? | Yes (Integral) | TILT ADJUSTMENT ANGLE: | Not Applicable |
| LUMINOUS FLUX: | 528.18 (lm) | ROTATION ADJUSTMENT ANGLE: | Not Applicable |
| COLOUR TEMP: | 2700 (K) | AVERAGE LIFESPAN: | 40,000 (Hrs) |
| CRI: | 80 | L70: | To Be Advised |
| R9: | -2.0 | | |

ELECTRICAL

| | | | |
|-------------------------------|---------------------------------|-----------------------------------|----------------|
| SWITCHED: | No | SUPPLY FREQUENCY: | 50/60 (Hz) |
| DIMMABLE: | Yes | DRIVER / BALLAST VOLTAGE: | 210-250 (V) |
| DIMMING METHOD: | Phase - Leading & Trailing Edge | DRIVER AVERAGE LIFESPAN: | 40000 (Hrs) |
| DRIVER OUTPUT CURRENT: | Not Applicable | EFFICACY: | 68.59 (lm/W) |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER / BALLAST INCLUDED? | Yes (Integral) |

ADDITIONAL INFORMATION

CE



BOX QUANTITY x 20

PRODUCT ELEVATIONS

