TANGO 2700K **7526**

astro

SKU 1175010



PRODUCT SPECIFICATION

GENERAL

FINISH: Polished Stainless Steel CABLE LENGTH: Not Applicable MAIN MATERIAL: Metal - Stainless Steel **GROSS WEIGHT:** 0.2 (Kg) H:70mm W:70mm D:28.5mm **DIMENSIONS:** CLASS: CE (Class III) INSTALLATION ORIENTATION: Wall Mount IP RATING: IP65

 INSTALLATION ORIENTATION:
 Wall Mount
 IP RATING:
 IP65

 CUT OUT HOLE:
 62 (mm)
 BATHROOM ZONE:
 Zone 1, 2, 3

 RECESS DEPTH:
 100 (mm)
 VOLTAGE:
 Constant C

RECESS DEPTH: 100 (mm) VOLTAGE: Constant Current 350 (mA)

FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE: High Power LED MACADAM ELIPSE: 3-Step

To Be Advised

Not Applicable

MAXIMUM WATTAGE: UGR: Not Applicable MAXIMUM LAMP LENGTH: Not Applicable **BEAM ANGLE:** To Be Advised LAMP INCLUDED? Yes (Integral) TILT ADJUSTMENT ANGLE: Not Applicable **LUMINOUS FLUX:** To Be Advised **ROTATION ADJUSTMENT ANGLE:** Not Applicable **COLOUR TEMP:** 2700 (K) AVERAGE LIFESPAN: 60,000 (Hrs)

CRI: 80 L70: To Be Advised

ELECTRICAL

R9:

SWITCHED:NoSUPPLY FREQUENCY:Not ApplicableDIMMABLE:YesDRIVER/BALLAST VOLTAGE:Not ApplicableDIMMING METHOD:Control Gear DependantDRIVER AVERAGE LIFESPAN:Not Applicable

DRIVER OUTPUT CURRENT: Not Applicable EFFICACY: To Be Advised

ADDITIONAL INFORMATION

Œ



DRIVER/BALLAST INCLUDED?

BOX QUANTITY x 12

DRIVER OUTPUT VOLTAGE:

No

