
OLYMPUS TRIMLESS 7512

astro

SKU 1343002



PRODUCT SPECIFICATION

GENERAL

FINISH:Textured WhiteCABLE LENGTH:Not ApplicableMAIN MATERIAL:Metal - ZincGROSS WEIGHT:0.77 (Kg)DIMENSIONS:H: 306mm W: 100mm D: 43mmCLASS:CE (Class III)

DIMENSIONS:H: 306mm W: 100mm D: 43mmCLASS:CE (Class III)INSTALLATION ORIENTATION:Wall MountIP RATING:IP20

CUT OUT HOLE: L: 275mm W: 80mm BATHROOM ZONE: Zone 3

RECESS DEPTH: 45 (mm) VOLTAGE: Constant Current 350 (mA)

FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE: High Power LED **MACADAM ELIPSE:** 3-Step

MAXIMUM WATTAGE: 1W UGR: Not Applicable

MAXIMUM LAMP LENGTH: Not Applicable **BEAM ANGLE:** Not Applicable LAMP INCLUDED? Yes (Integral) TILT ADJUSTMENT ANGLE: Not Applicable **LUMINOUS FLUX:** 34.9 (lm) **ROTATION ADJUSTMENT ANGLE:** Not Applicable **COLOUR TEMP:** 2700 (K) AVERAGE LIFESPAN: 60,000 (Hrs) CRI: L70: To Be Advised

R9: To Be Advised

ELECTRICAL

SWITCHED:NoSUPPLY FREQUENCY:Not ApplicableDIMMABLE:YesDRIVER/BALLAST VOLTAGE:Not ApplicableDIMMING METHOD:Control Gear DependantDRIVER AVERAGE LIFESPAN:Not Applicable

DIMMING METHOD: Control Gear Dependant DRIVER AVERAGE LIFESPAN: Not Applicable

DRIVER OUTPUT CURRENT: Not Applicable EFFICACY: 15.79 (Im/W)

DRIVER OUTPUT VOLTAGE: Not Applicable DRIVER/BALLAST INCLUDED? No

ADDITIONAL INFORMATION

Œ

Product tested with 1275 - LED Driver CC 350mA 0.2-3.5W



BOX QUANTITY x 6

