



## PRODUCT SPECIFICATION

### GENERAL

<b>FINISH:</b>	Bronze	<b>CABLE LENGTH:</b>	1000 (mm)
<b>MAIN MATERIAL:</b>	Metal - Aluminium	<b>GROSS WEIGHT:</b>	1.41 (Kg)
<b>DIMENSIONS:</b>	H: 265mm W: 600mm D: 185mm	<b>CLASS:</b>	CE (Class III)
<b>INSTALLATION ORIENTATION:</b>	Wall Mount - Horizontal	<b>IP RATING:</b>	IP20
<b>CUT OUT HOLE:</b>	Not Applicable	<b>BATHROOM ZONE:</b>	Zone 3
<b>RECESS DEPTH:</b>	Not Applicable	<b>VOLTAGE:</b>	Constant Voltage 12V
<b>FIRE RATING:</b>	Not Applicable	<b>PRODUCT F MARK:</b>	Suitable for mounting on flammable materials

### LAMP


<b>LIGHT SOURCE:</b>	LED Strip	<b>MACADAM ELIPSE:</b>	+/- 100K
<b>MAXIMUM WATTAGE:</b>	8.4W	<b>UGR:</b>	To Be Advised
<b>MAXIMUM LAMP LENGTH:</b>	Not Applicable	<b>BEAM ANGLE:</b>	To Be Advised
<b>LAMP INCLUDED?</b>	Yes	<b>TILT ADJUSTMENT ANGLE:</b>	40 (Degrees)
<b>LUMINOUS FLUX:</b>	219.29 (lm)	<b>ROTATION ADJUSTMENT ANGLE:</b>	0 (Degrees)
<b>COLOUR TEMP:</b>	2700 (K)	<b>AVERAGE LIFESPAN:</b>	Not Applicable
<b>CRI:</b>	80	<b>L70:</b>	To Be Advised
<b>R9:</b>	-2.0		

### ELECTRICAL

<b>SWITCHED:</b>	No	<b>SUPPLY FREQUENCY:</b>	Not Applicable
<b>DIMMABLE:</b>	Yes	<b>DRIVER / BALLAST VOLTAGE:</b>	Not Applicable
<b>DIMMING METHOD:</b>	Control Gear Dependent	<b>DRIVER AVERAGE LIFESPAN:</b>	Not Applicable
<b>DRIVER OUTPUT CURRENT:</b>	Not Applicable	<b>EFFICACY:</b>	20.3 (lm/W)
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER / BALLAST INCLUDED?</b>	No

## ADDITIONAL INFORMATION

Product tested with 1613 - LED Driver CC 250/350/500/700mA DALI Dim



BOX QUANTITY x 6



# PRODUCT ELEVATIONS

---

