

CAN 50 RECESSED 6170

SKU 1396008

astro



PRODUCT SPECIFICATION

GENERAL

FINISH:	Matt Black	CABLE LENGTH:	200 (mm)
MAIN MATERIAL:	Metal - Aluminium	GROSS WEIGHT:	0.43 (Kg)
DIMENSIONS:	H: 124mm DIA: 80mm	CLASS:	CE (Class I)
INSTALLATION ORIENTATION:	Ceiling Mount Install in To Existing Ceiling	IP RATING:	IP20
CUT OUT HOLE:	60mm/2-3/8"	BATHROOM ZONE:	Zone 3
RECESS DEPTH:	60 (mm)	VOLTAGE:	Mains 230V
FIRE RATING:	To Be Advised	PRODUCT F MARK:	Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE:	LED Module	MACADAM ELLIPSE:	3-Step
MAXIMUM WATTAGE:	7.7W	UGR:	To Be Advised
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	30.35 (Degrees)
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	90 (Degrees)
LUMINOUS FLUX:	501.6 (lm)	ROTATION ADJUSTMENT ANGLE:	330 (Degrees)
COLOUR TEMP:	3000 (K)	AVERAGE LIFESPAN:	40,000 (Hrs)
CRI:	80	L70:	>33,000 (Hrs)
R9:	3.0		

ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	50/60 (Hz)
DIMMABLE:	Yes	DRIVER / BALLAST VOLTAGE:	220-240 (V)
DIMMING METHOD:	Phase - Leading Edge	DRIVER AVERAGE LIFESPAN:	Not Applicable
DRIVER OUTPUT CURRENT:	Not Applicable	EFFICACY:	65.14 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER / BALLAST INCLUDED?	Not Applicable

ADDITIONAL INFORMATION

CE



BOX QUANTITY x 30

PRODUCT ELEVATIONS

GB Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

FR Veuillez noter que certaines dimensions peuvent varier légèrement en raison des tolérances de fabrication, y compris l'entrée de câble et les trous de fixation.

DE Bitte beachten Sie, dass die Maße Fertigungstoleranzen unterliegen und daher in geringem Umfang von der angegebenen Größe abweichen können. Dies gilt auch für Kabeleingänge und Befestigungslöcher.

IT Si prega notare che possono esserci piccole variazioni in alcune dimensioni dovute alle tolleranze di produzione, queste includono l'ingresso del cavo e i fori di fissaggio.

