

## PRODUCT SPECIFICATION

### GENERAL

<b>FINISH:</b>	Polished Chrome	<b>CABLE LENGTH:</b>	Not applicable
<b>MAIN MATERIAL:</b>	Metal - Mild Steel	<b>GROSS WEIGHT:</b>	2.567 (kg)
<b>DIMENSIONS:</b>	H: 600mm W: 80mm D: 80mm	<b>CLASS:</b>	CE (Class II)
<b>INSTALLATION ORIENTATION:</b>	Wall Mount	<b>IP RATING:</b>	IP44
<b>CUT OUT HOLE:</b>	Not Applicable	<b>BATHROOM ZONE:</b>	Zone 2, 3
<b>RECESS DEPTH:</b>	Not Applicable	<b>VOLTAGE:</b>	Mains 230 (V)
<b>FIRE RATING:</b>	Not Applicable	<b>PRODUCT F MARK:</b>	Suitable for mounting on flammable materials

### LAMP

<b>LIGHT SOURCE:</b>	T5 HO	<b>MACADAM ELIPSE:</b>	Not Applicable
<b>MAXIMUM WATTAGE:</b>	24W	<b>UGR:</b>	-17 (UGR)
<b>MAXIMUM LAMP LENGTH:</b>	Not Applicable	<b>BEAM ANGLE:</b>	Not Applicable
<b>LAMP INCLUDED?</b>	No	<b>TILT ADJUSTMENT ANGLE:</b>	Not Applicable
<b>LUMINOUS FLUX:</b>	530.2 (lm)	<b>ROTATION ADJUSTMENT ANGLE:</b>	Not Applicable
<b>COLOUR TEMP:</b>	Lamp Dependent	<b>AVERAGE LIFESPAN:</b>	19,000 (hrs)
<b>CRI:</b>	80	<b>L70:</b>	Not Applicable
<b>R9:</b>	-17		


### ELECTRICAL

<b>SWITCHED:</b>	No	<b>SUPPLY FREQUENCY:</b>	50/60 (Hz)
<b>DIMMABLE:</b>	No	<b>DRIVER/BALLAST VOLTAGE:</b>	220-240 (V)
<b>DIMMING METHOD:</b>	Not Applicable	<b>DRIVER AVERAGE LIFESPAN:</b>	Not Applicable
<b>DRIVER OUTPUT CURRENT:</b>	Not Applicable	<b>EFFICACY:</b>	25.25 (lm/W)
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER INCLUDED?</b>	Yes (Integral)

## ADDITIONAL INFORMATION



This product is not suitable for use with a PIR motion detector.



BOX QUANTITY X6

# PRODUCT ELEVATIONS

---

