

PRODUCT SPECIFICATION

GENERAL

FINISH:	Polished Chrome	CABLE LENGTH:	Not Applicable
MAIN MATERIAL:	Metal - Zinc	GROSS WEIGHT:	1.05 (kg)
DIMENSIONS:	H: 329mm W: 50mm D: 90mm	CLASS:	CE (Class II)
INSTALLATION ORIENTATION:	Wall Mount - Vertical	IP RATING:	IP44
CUT OUT HOLE:	Not Applicable	BATHROOM ZONE:	Zone 2, 3
RECESS DEPTH:	Not Applicable	VOLTAGE:	Mains 230V
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Suitable for mounting on flammable materials


LAMP

LIGHT SOURCE:	Mid-Power LED	MACADAM ELIPSE:	3-Step
MAXIMUM WATTAGE:	3.2W	UGR:	Not Applicable
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	Not Applicable
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	Not Applicable
LUMINOUS FLUX:	279.8 (lm)	ROTATION ADJUSTMENT ANGLE:	Not Applicable
COLOUR TEMP:	3000 (K)	AVERAGE LIFESPAN:	60,000 (Hrs)
CRI:	80	L70:	To Be Advised
R9:	15.4		

ELECTRICAL



SWITCHED:	No	SUPPLY FREQUENCY:	50/60 (Hz)
DIMMABLE:	No	DRIVER/BALLAST VOLTAGE:	100-240 (V)
DIMMING METHOD:	Not Applicable	DRIVER AVERAGE LIFESPAN:	30,000 (Hrs)
DRIVER OUTPUT CURRENT:	350 (mA)	EFFICACY:	66.78 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER/BALLAST INCLUDED?	Yes (Integral)

ADDITIONAL INFORMATION





BOX QUANTITY X6

PRODUCT ELEVATIONS



FRONT VIEW



BACK VIEW