

## PRODUCT SPECIFICATION

### GENERAL

<b>FINISH:</b>	White	<b>GROSS WEIGHT:</b>	1.43 (lbs)
<b>MAIN MATERIAL:</b>	Metal - Aluminium	<b>CLASS:</b>	ETL (Class 2)
<b>DIMENSIONS:</b>	H:176mm W: 90mm D:75mm H:6.92" W:3.54" D:2.95"	<b>LISTING LOCATION:</b>	Damp
<b>INSTALLATION ORIENTATION:</b>	Ceiling Mount	<b>FITTING METHOD:</b>	Recessed in Drywall Ceiling
<b>CUT OUT HOLE:</b>	L: 160mm / 6.29" W: 80mm / 3.14"	<b>ADA COMPLIANT:</b>	Yes
<b>RECESS DEPTH:</b>	150mm / 5.9"	<b>IC RATING:</b>	Non IC Rated
<b>FIRE RATING:</b>	Not Applicable	<b>VOLTAGE:</b>	Constant Current 350 (mA)
<b>CABLE LENGTH:</b>	Not Applicable	<b>PRODUCT F MARK:</b>	Suitable for mounting on flammable materials


### LAMP

<b>LIGHT SOURCE:</b>	COB LED	<b>MACADAM ELIPSE:</b>	3 - Step
<b>MAXIMUM WATTAGE:</b>	2 x 10W	<b>UGR:</b>	To Be Advised
<b>MAXIMUM LAMP LENGTH:</b>	Not Applicable	<b>BEAM ANGLE:</b>	20.2 (Degrees)
<b>LAMP INCLUDED?</b>	Yes (Integral)	<b>TILT ADJUSTMENT ANGLE:</b>	Not Applicable
<b>DELIVERED LUMENS:</b>	1191 (lm)	<b>ROTATION ADJUSTMENT ANGLE:</b>	Not Applicable
<b>COLOR TEMP:</b>	3000 (K)	<b>AVERAGE LIFESPAN:</b>	50,000 (Hrs)
<b>CRI:</b>	80	<b>L70:</b>	To Be Advised
<b>R9:</b>	14		

### ELECTRICAL

<b>SWITCHED:</b>	No	<b>SUPPLY FREQUENCY:</b>	Not Applicable
<b>DIMMABLE:</b>	Yes	<b>DRIVER/BALLAST VOLTAGE:</b>	Not Applicable
<b>DIMMING METHOD:</b>	Control Gear Dependant	<b>DRIVER AVERAGE LIFESPAN:</b>	Not Applicable
<b>DRIVER OUTPUT CURRENT:</b>	Not Applicable	<b>EFFICACY:</b>	46.98 (lm/w)
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER INCLUDED?</b>	No

## ADDITIONAL INFORMATION



BOX QUANTITY X20

# PRODUCT ELEVATIONS

---

