DUNBAR 160 LED **7944** SKU 1384002

astro



PRODUCT SPECIFICATION

GENERAL

| FINISH: | White | CABLE LENGTH: | Not Applicable |
|---------------------------|------------------------|----------------------------|---|
| MAIN MATERIAL: | Metal - Aluminium | GROSS WEIGHT: | 0.9 (Kg) |
| DIMENSIONS: | H:160mm W:80mm D:100mm | CLASS: | CE (Class I) |
| INSTALLATION ORIENTATION: | Wall Mount | IP RATING: | IP65 |
| CUT OUT HOLE: | Not Applicable | BATHROOM ZONE: | Not Applicable |
| RECESS DEPTH: | Not Applicable | VOLTAGE: | Mains 230V |
| FIRE RATING: | Not Applicable | PRODUCT F MARK: | Suitable for mounting on flammable materia |
| LAMP | | | |
| LIGHT SOURCE: | High-Power LED | MACADAM ELLIPSE: | 3-Step |
| MAXIMUM WATTAGE: | 2 x 3W | UGR: | To Be Advised |
| MAXIMUM LAMP LENGTH: | Not Applicable | BEAM ANGLE: | To Be Advised |
| LAMP INCLUDED? | Yes (Integral) | TILT ADJUSTMENT ANGLE: | Not Applicable |
| LUMINOUS FLUX: | 134.14 (lm) | ROTATION ADJUSTMENT ANGLE: | Not Applicable |
| COLOUR TEMP: | 3000 (K) | AVERAGE LIFESPAN: | To Be Advised |
| CRI: | 80 | L70: | To Be Advised |
| R9: | 13.1 | | |
| ELECTRICAL | | | |
| SWITCHED: | No | SUPPLY FREQUENCY: | 50/60 (Hz) |
| DIMMABLE: | No | DRIVER/BALLAST VOLTAGE: | 220-240 (V) |
| DIMMING METHOD: | Not Applicable | DRIVER AVERAGE LIFESPAN: | 60,000 (Hrs) |
| DRIVER OUTPUT CURRENT: | 700 (mA) | EFFICACY: | 19.70 (lm/W) |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER/BALLAST INCLUDED? | Yes (Integral) |

ADDITIONAL INFORMATION


ONEROUS ENVIRONMENTS


All of our exterior products are covered by a 3 year guarantee; however this does not apply to any that are installed within 5 miles of the coast. For these environments, please filter products on the Astro website by "Coastal".




BOX QUANTITY X6

CE







T: +44 (0) 1279 427001