



PRODUCT SPECIFICATION

GENERAL

| | | | |
|----------------------------------|---------------------------|------------------------|--|
| FINISH: | White | CABLE LENGTH: | 1000mm |
| MAIN MATERIAL: | Metal - Aluminium | GROSS WEIGHT: | 1.026 (Kg) |
| DIMENSIONS: | H:177mm DIA:146mm | CLASS: | CE (Class III) |
| INSTALLATION ORIENTATION: | Install in to new ceiling | IP RATING: | IP65 |
| CUT OUT HOLE: | 95mm/3-3/4" | BATHROOM ZONE: | Zone 1, 2, 3 |
| RECESS DEPTH: | 177mm | VOLTAGE: | Constant Current 250 (mA) |
| FIRE RATING: | 90 min | PRODUCT F MARK: | Suitable for mounting on flammable materials |

LAMP

| | | | |
|-----------------------------|----------------|-----------------------------------|----------------|
| LIGHT SOURCE: | COB LED | MACADAM ELLIPSE: | 3-Step |
| MAXIMUM WATTAGE: | 9.1W | UGR: | To Be Advised |
| MAXIMUM LAMP LENGTH: | Not Applicable | BEAM ANGLE: | 14 (Degrees) |
| LAMP INCLUDED? | Yes (Integral) | TILT ADJUSTMENT ANGLE: | Not Applicable |
| LUMINOUS FLUX: | 888.5 (lm) | ROTATION ADJUSTMENT ANGLE: | Not Applicable |
| COLOUR TEMP: | 3000 (K) | AVERAGE LIFESPAN: | To Be Advised |
| CRI: | 80 | L70: | To Be Advised |
| R9: | 12 | | |

ELECTRICAL

| | | | |
|-------------------------------|------------------------|---------------------------------|----------------|
| SWITCHED: | No | SUPPLY FREQUENCY: | Not Applicable |
| DIMMABLE: | Yes | DRIVER/BALLAST VOLTAGE: | Not Applicable |
| DIMMING METHOD: | Control Gear Dependant | DRIVER AVERAGE LIFESPAN: | Not Applicable |
| DRIVER OUTPUT CURRENT: | Not Applicable | EFFICACY: | 103.3 (lm/W) |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER/BALLAST INCLUDED? | Not Applicable |

ADDITIONAL INFORMATION



BOX QUANTITY X8

PRODUCT ELEVATIONS



95mm / 3-4/4"

