
OBSCURA SQUARE **5766** SKU 1381002

astro



PRODUCT SPECIFICATION

GENERAL

FINISH:Polished ChromeCABLE LENGTH:Not ApplicableMAIN MATERIAL:Metal - AluminiumGROSS WEIGHT:0.49 (Kg)DIMENSIONS:H: 84mm W: 84mm D: 85mmCLASS:CE (Class III)

DIMENSIONS:H: 84mm W: 84mm D: 85mmCLASS:CE (Class III)INSTALLATION ORIENTATION:Ceiling MountIP RATING:IP65CUT OUT HOLE:70mm/2-3/4"BATHROOM ZONE:Zone 1, 2, 3

CUT OUT HOLE: 70mm/2-3/4" BATHROOM ZONE: Zone 1, 2, 3

RECESS DEPTH: Not Applicable VOLTAGE: Mains 230V

FIRE RATING: 90 min PRODUCT F MARK: Not suitable for covering with thermal insulation. Suitable for mounting on

L70:

LAMP

LIGHT SOURCE: COB LED MACADAM ELIPSE: 3-Step UGR: MAXIMUM WATTAGE: 6.5W To Be Advised MAXIMUM LAMP LENGTH: Not Applicable **BEAM ANGLE:** 40 (Degrees) LAMP INCLUDED? TILT ADJUSTMENT ANGLE: Yes (Integral) Not Applicable **LUMINOUS FLUX:** 332.09 (lm) **ROTATION ADJUSTMENT ANGLE:** Not Applicable **COLOUR TEMP:** 2700 (K) AVERAGE LIFESPAN: 40,000 (Hrs)

CRI: 82 **R9:** 6.0

ELECTRICAL

SWITCHED: SUPPLY FREQUENCY: No 50 (Hz) DIMMABLE: Yes DRIVER/BALLAST VOLTAGE: 220-240 (V) **DIMMING METHOD:** Phase & 1-10V DRIVER AVERAGE LIFESPAN: 50,000 (Hrs) DRIVER OUTPUT CURRENT: 180 (mA) EFFICACY: 43.7 (lm/W)

DRIVER OUTPUT VOLTAGE: Not Applicable DRIVER/BALLAST INCLUDED? Yes

ADDITIONAL INFORMATION





BOX QUANTITY x 20


CE


flammable materials.

To Be Advised









T: +44 (0) 1279 427001 sales@astrolighting.com www.astrolighting.com