

OBSCURA ROUND 5768

SKU 1381001

astro



PRODUCT SPECIFICATION

GENERAL

FINISH:	Polished Chrome	CABLE LENGTH:	Not Applicable
MAIN MATERIAL:	Metal - Aluminium	GROSS WEIGHT:	0.46 (Kg)
DIMENSIONS:	D: 85mm Dia: 84mm	CLASS:	CE (Class III)
INSTALLATION ORIENTATION:	Ceiling Mount	IP RATING:	IP65
CUT OUT HOLE:	70mm/2-3/4"	BATHROOM ZONE:	Zone 1, 2, 3
RECESS DEPTH:	Not Applicable	VOLTAGE:	Mains 230V
FIRE RATING:	90 min	PRODUCT F MARK:	Not suitable for covering with thermal insulation. Suitable for mounting on flammable materials.

LAMP

LIGHT SOURCE:	COB LED	MACADAM ELIPSE:	3-Step
MAXIMUM WATTAGE:	6.5W	UGR:	To Be Advised
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	40 (Degrees)
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	Not Applicable
LUMINOUS FLUX:	383 (lm)	ROTATION ADJUSTMENT ANGLE:	Not Applicable
COLOUR TEMP:	2700 (K)	AVERAGE LIFESPAN:	40,000 (Hrs)
CRI:	82	L70:	To Be Advised
R9:	10.1		

ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	50 (Hz)
DIMMABLE:	Yes	DRIVER/BALLAST VOLTAGE:	220-240 (V)
DIMMING METHOD:	Phase & 1-10V	DRIVER AVERAGE LIFESPAN:	50,000 (Hrs)
DRIVER OUTPUT CURRENT:	180 (mA)	EFFICACY:	46.72 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER/BALLAST INCLUDED?	Yes

ADDITIONAL INFORMATION

CE



BOX QUANTITY x 20

PRODUCT ELEVATIONS

