OBSCURA ROUND **5767** sku 1381003



PRODUCT SPECIFICATION


GENERAL

| FINISH: | Matt White | CABLE LENGTH: | Not Applicable |
|---------------------------|-------------------|----------------------------|---|
| MAIN MATERIAL: | Metal - Aluminium | GROSS WEIGHT: | 0.49 (Kg) |
| DIMENSIONS: | D: 85mm Dia: 84mm | CLASS: | CE (Class III) |
| INSTALLATION ORIENTATION: | Ceiling Mount | IP RATING: | IP65 |
| CUT OUT HOLE: | 70mm/2-3/4″ | BATHROOM ZONE: | Zone 1, 2, 3 |
| RECESS DEPTH: | Not Applicable | VOLTAGE: | Mains 230V |
| FIRE RATING: | 90 min | PRODUCT F MARK: | Not suitable for covering with thermal insulation. Suitable for mounting or flammable materials. |
| LAMP | | | |
| LIGHT SOURCE: | COB LED | MACADAM ELIPSE: | 3-Step |
| MAXIMUM WATTAGE: | 6.5W | UGR: | To Be Advised |
| MAXIMUM LAMP LENGTH: | Not Applicable | BEAM ANGLE: | 40 (Degrees) |
| LAMP INCLUDED? | Yes (Integral) | TILT ADJUSTMENT ANGLE: | Not Applicable |
| LUMINOUS FLUX: | 383 (lm) | ROTATION ADJUSTMENT ANGLE: | Not Applicable |
| COLOUR TEMP: | 2700 (K) | AVERAGE LIFESPAN: | 40,000 (Hrs) |
| CRI: | 82 | L70: | To Be Advised |
| R9: | 10.1 | | |
| ELECTRICAL | | | |
| SWITCHED: | No | SUPPLY FREQUENCY: | 50 (Hz) |
| DIMMABLE: | Yes | DRIVER / BALLAST VOLTAGE: | 220-240 (V) |
| DIMMING METHOD: | Phase & 1-10V | DRIVER AVERAGE LIFESPAN: | 50,000 (Hrs) |
| DRIVER OUTPUT CURRENT: | 180 (mA) | EFFICACY: | 46.72 (lm/W) |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER/BALLAST INCLUDED? | Yes |
| ADDITIONAL INFORI | | | C |





BOX QUANTITY x 20


PRODUCT ELEVATIONS



Ø68 cut out







T: +44 (0) 1279 427001

sales@astrolighting.com

www.astrolighting.com