
DUNBAR 255 LED 7993 SKU 1384006

astro



PRODUCT SPECIFICATION

GENERAL

FINISH:	
MAIN MATERIAL:	
DIMENSIONS:	
INSTALLATION ORIENTATION:	

CUT OUT HOLE: **RECESS DEPTH:** FIRE RATING:

LAMP

LIGHT SOURCE:
MAXIMUM WATTAGE:
MAXIMUM LAMP LENGTH:
LAMP INCLUDED?
LUMINOUS FLUX:
COLOUR TEMP:
CRI:
R9:

Metal - Aluminium H: 255mm W: 104mm D: 125mm Wall Mount - Horizontal (reduced IP rating) / Vertical Not Applicable Not Applicable Not Applicable

Textured Painted Silver

CABLE LENGTH: GROSS WEIGHT: CLASS: **IP RATING:** BATHROOM ZONE: VOLTAGE: PRODUCT F MARK: Not Applicable 1.46 (Kg) CE (Class I) IP65 Zone 1, 2, 3 Mains 230V Suitable for mounting on flammable materials

MACADAM ELLIPSE: UGR: **BEAM ANGLE:** TILT ADJUSTMENT ANGLE: ROTATION ADJUSTMENT ANGLE: AVERAGE LIFESPAN: L70:

SUPPLY FREQUENCY:

EFFICACY:

DRIVER / BALLAST VOLTAGE:

DRIVER AVERAGE LIFESPAN:

DRIVER/BALLAST INCLUDED?

3-Step To Be Advised To Be Advised Not Applicable Not Applicable 36,300 (Hrs) To Be Advised

50/60 (Hz)

100-240 (V)

Not Applicable

40.36 (lm/W)

Yes (Integral)

ELECTRICAL

SWITCHED: DIMMABLE: DIMMING METHOD: DRIVER OUTPUT CURRENT: DRIVER OUTPUT VOLTAGE:

No Not Applicable 350 (mA) Not Applicable

COB LED

Not Applicable

Yes (Integral)

302.67 (lm)

3000 (K)

80

14.1

No

7.5W

ADDITIONAL INFORMATION

ONEROUS ENVIRONMENTS


All of our exterior products are covered by a 3 year guarantee; however this does not apply to any that are installed within 5 miles of the coast. For these environments, please filter products on the Astro website by "Coastal".





BOX QUANTITY x 6


CE

PRODUCT ELEVATIONS









T: +44 (0) 1279 427001

sales@astrolighting.com