



PRODUCT SPECIFICATION

GENERAL

| | | | |
|----------------------------------|----------------------------|------------------------|----------------|
| FINISH: | Textured Black | CABLE LENGTH: | Not Applicable |
| MAIN MATERIAL: | Metal - Aluminium | GROSS WEIGHT: | 1.05 (Kg) |
| DIMENSIONS: | D: 55mm DIA: 150mm | CLASS: | CE (Class I) |
| INSTALLATION ORIENTATION: | Wall Mount / Ceiling Mount | IP RATING: | IP65 |
| CUT OUT HOLE: | Not Applicable | BATHROOM ZONE: | Zone 1, 2, 3 |
| RECESS DEPTH: | Not Applicable | VOLTAGE: | Mains 230V |
| FIRE RATING: | Not Applicable | PRODUCT F MARK: | Not Applicable |

LAMP

| | | | |
|-----------------------------|----------------|-----------------------------------|----------------|
| LIGHT SOURCE: | LED | MACADAM ELLIPSE: | To Be Advised |
| MAXIMUM WATTAGE: | 8.1W | UGR: | Not Applicable |
| MAXIMUM LAMP LENGTH: | Not Applicable | BEAM ANGLE: | Not Applicable |
| LAMP INCLUDED? | Yes (Integral) | TILT ADJUSTMENT ANGLE: | Not Applicable |
| LUMINOUS FLUX: | 565.6 (lm) | ROTATION ADJUSTMENT ANGLE: | Not Applicable |
| COLOUR TEMP: | 3000 (K) | AVERAGE LIFESPAN: | 50,000 (Hrs) |
| CRI: | >80 | L70: | To Be Advised |
| R9: | 9.0 | | |


ELECTRICAL

| | | | |
|-------------------------------|----------------|-----------------------------------|----------------|
| SWITCHED: | No | SUPPLY FREQUENCY: | 50/60 (Hz) |
| DIMMABLE: | No | DRIVER / BALLAST VOLTAGE: | 100-240 (V) |
| DIMMING METHOD: | Not Applicable | DRIVER AVERAGE LIFESPAN: | To Be Advised |
| DRIVER OUTPUT CURRENT: | 350 (mA) | EFFICACY: | 69.83 (lm/W) |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER / BALLAST INCLUDED? | Yes (Integral) |

ADDITIONAL INFORMATION

ONEROUS ENVIRONMENTS

All of our exterior products are covered by a 3 year guarantee; however this does not apply to any that are installed within 5 miles of the coast. For these environments, please filter products on the Astro website by "Coastal".



BOX QUANTITY x 12



PRODUCT ELEVATIONS

