KIWI WALL 8008

SKU 1390001

astro

PRODUCT SPECIFICATION

GENERAL

|			
FINISH:	Polished Copper	CABLE LENGTH:	Not Applicable
MAIN MATERIAL:	Metal - Zinc	GROSS WEIGHT:	1.364 (Kg)
DIMENSIONS:	H: 356mm W: 130mm D: 170mm	CLASS:	CE (Class II)
INSTALLATION ORIENTATION:	Wall Mount - Downlight/Uplight	IP RATING:	IP44
CUT OUT HOLE:	Not Applicable	BATHROOM ZONE:	Zone 2, 3
RECESS DEPTH:	Not Applicable	VOLTAGE:	Mains 230V
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE:	COB LED	MACADAM ELLIPSE:	3-Step
MAXIMUM WATTAGE:	7.2W	UGR:	Not Applicable
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	Not Applicable
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	Not Applicable
LUMINOUS FLUX:	567.4 (lm)	ROTATION ADJUSTMENT ANGLE:	Not Applicable
COLOUR TEMP:	2700 (K)	AVERAGE LIFESPAN:	36,300 (Hrs)
CRI:	80	L70:	To Be Advised
R9:	9.0		

ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	50/60 (Hz)
DIMMABLE:	No	DRIVER/BALLAST VOLTAGE:	100-240 (V)
DIMMING METHOD:	Not Applicable	DRIVER AVERAGE LIFESPAN:	30,000 (Hrs)
DRIVER OUTPUT CURRENT:	350 (mA)	EFFICACY:	78.81 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER/BALLAST INCLUDED?	Yes (Integral)

ADDITIONAL INFORMATION

CE

BOX QUANTITY x 4

170

Ø130

356

Ø100

35

70

10

27