

ELIS COASTAL SINGLE 8006

SKU 1331005

astro



PRODUCT SPECIFICATION

GENERAL

FINISH:	Antique Brass	CABLE LENGTH:	Not Applicable
MAIN MATERIAL:	Metal - Brass (H62)	GROSS WEIGHT:	1.596 (Kg)
DIMENSIONS:	H: 141mm W: 141mm D: 51mm	CLASS:	CE (Class I)
INSTALLATION ORIENTATION:	Wall Mount - Downlight/Uplight	IP RATING:	IP54
CUT OUT HOLE:	Not Applicable	BATHROOM ZONE:	Zone 1, 2, 3
RECESS DEPTH:	Not Applicable	VOLTAGE:	Mains 230V
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Suitable for mounting on flammable materials

LAMP


LIGHT SOURCE:	High-Power LED	MACADAM ELLIPSE:	6-Step
MAXIMUM WATTAGE:	4.4W	UGR:	Not Applicable
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	Not Applicable
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	Not Applicable
LUMINOUS FLUX:	244.8 (lm)	ROTATION ADJUSTMENT ANGLE:	Not Applicable
COLOUR TEMP:	3000 (K)	AVERAGE LIFESPAN:	60,500 (Hrs)
CRI:	80	L70:	Not Applicable
R9:	5.4		

ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	50/60 (Hz)
DIMMABLE:	No	DRIVER/BALLAST VOLTAGE:	100-240 (V)
DIMMING METHOD:	Not Applicable	DRIVER AVERAGE LIFESPAN:	Not Applicable
DRIVER OUTPUT CURRENT:	350 (mA)	EFFICACY:	55.64 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER/BALLAST INCLUDED?	Yes (Integral)

ADDITIONAL INFORMATION

Our Coastal collection is designed to withstand whatever the weather can throw at it. It is constructed from solid brass which will acquire a natural patina over time that adds to the charm of the material. Suitable for use by the coast and other exposed areas, the collection combines outstanding durability with striking design.



BOX QUANTITY x 12



PRODUCT ELEVATIONS

CARE INSTRUCTIONS

Please note the patina caused through aging can be polished-back to restore the original finish if desired. We recommend that the product is rinsed with fresh water periodically to remove any excess salt deposits. A ten-year warranty is offered on all products within the Coastal collection, except those that have integral LEDs or drivers, which are subject to our standard three-year warranty.

