



PRODUCT SPECIFICATION

GENERAL

FINISH:	Matt White	CABLE LENGTH:	1000 (mm)
MAIN MATERIAL:	Metal - Aluminium	GROSS WEIGHT:	0.748 (Kg)
DIMENSIONS:	H:163mm DIA: 121mm	CLASS:	CE (Class III)
INSTALLATION ORIENTATION:	Install in to new ceiling	IP RATING:	IP65
CUT OUT HOLE:	DIA: 70mm/2-3/4"	BATHROOM ZONE:	Zone 1, 2, 3
RECESS DEPTH:	163 (mm)	VOLTAGE:	Constant Current 700 (mA)
FIRE RATING:	90 (min)	PRODUCT F MARK:	Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE:	COB LED	MACADAM ELLIPSE:	3-Step
MAXIMUM WATTAGE:	6.8W	UGR:	To Be Advised
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	26 (Degrees)
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	Not Applicable
LUMINOUS FLUX:	525.44 (lm)	ROTATION ADJUSTMENT ANGLE:	Not Applicable
COLOUR TEMP:	3000K	AVERAGE LIFESPAN:	36,300 (Hrs)
CRI:	80	L70:	To Be Advised
R9:	7.8		


ELECTRICAL

SWITCHED:	Not Applicable	SUPPLY FREQUENCY:	Not Applicable
DIMMABLE:	Yes	DRIVER/BALLAST VOLTAGE:	Not Applicable
DIMMING METHOD:	Control Gear Dependent	DRIVER AVERAGE LIFESPAN:	Not Applicable
DRIVER OUTPUT CURRENT:	Not Applicable	EFFICACY:	57.74 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER/BALLAST INCLUDED?	No

ADDITIONAL INFORMATION



Product tested with 1836 - LED Driver CC 250/350/500/700mA DALI Dim



BOX QUANTITY x 12

PRODUCT ELEVATIONS

