



PRODUCT SPECIFICATION

GENERAL

FINISH:	Matt Concrete	CABLE LENGTH:	Not Applicable
MAIN MATERIAL:	Concrete - Cast	GROSS WEIGHT:	1.60 (Kg)
DIMENSIONS:	H: 160mm W: 84mm D: 107mm	CLASS:	CE (Class I)
INSTALLATION ORIENTATION:	Wall Mount - Vertical	IP RATING:	IP65
CUT OUT HOLE:	Not Applicable	BATHROOM ZONE:	Zone 1, 2, 3
RECESS DEPTH:	Not Applicable	VOLTAGE:	Mains 230V
FIRE RATING:	To Be Advised	PRODUCT F MARK:	To Be Advised

LAMP

LIGHT SOURCE:	High-Power LED	MACADAM ELLIPSE:	3-Step
MAXIMUM WATTAGE:	6.1W	UGR:	To Be Advised
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	49 (Degrees)
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	Not Applicable
LUMINOUS FLUX:	117.44 (lm)	ROTATION ADJUSTMENT ANGLE:	Not Applicable
COLOUR TEMP:	3000 (K)	AVERAGE LIFESPAN:	60,000 (Hrs)
CRI:	80	L70:	>60,000 (Hrs)
R9:	18.2		


ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	50/60 (Hz)
DIMMABLE:	No	DRIVER / BALLAST VOLTAGE:	220-240 (V)
DIMMING METHOD:	Not Applicable	DRIVER AVERAGE LIFESPAN:	60,000 (Hrs)
DRIVER OUTPUT CURRENT:	700 (mA)	EFFICACY:	19.25 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER / BALLAST INCLUDED?	Yes (Integral)

ADDITIONAL INFORMATION

ONEROUS ENVIRONMENTS

All of our exterior products are covered by a 3 year guarantee; however this does not apply to any that are installed within 5 miles of the coast. For these environments, please filter products on the Astro website by "Coastal".



BOX QUANTITY x 10



PRODUCT ELEVATIONS

GB Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

FR Veuillez noter que certaines dimensions peuvent varier légèrement en raison des tolérances de fabrication, y compris l'entrée de câble et les trous de fixation.

DE Bitte beachten Sie, dass die Maße Fertigungstoleranzen unterliegen und daher in geringem Umfang von der angegebenen Größe abweichen können. Dies gilt auch für Kabeleingänge und Befestigungslöcher.

IT Si prega notare che possono esserci piccole variazioni in alcune dimensioni dovute alle tolleranze di produzione, queste includono l'ingresso del cavo e i fori di fissaggio.

