

# BAYVILLE SINGLE SPOT 8305

SKU 1401004

astro



## PRODUCT SPECIFICATION

### GENERAL

|                                  |                                  |                        |  |
|----------------------------------|----------------------------------|------------------------|--|
| <b>FINISH:</b>                   | Textured White                   | <b>CABLE LENGTH:</b>   | Not Applicable                                   |
| <b>MAIN MATERIAL:</b>            | Metal - Aluminium                | <b>GROSS WEIGHT:</b>   | 0.678 (Kg)                                       |
| <b>DIMENSIONS:</b>               | H: 100mm W: 95mm D: 125mm        | <b>CLASS:</b>          | CE (Class I)                                     |
| <b>INSTALLATION ORIENTATION:</b> | Wall Mount - Horizontal/Vertical | <b>IP RATING:</b>      | IP65   |
| <b>CUT OUT HOLE:</b>             | Not Applicable                   | <b>BATHROOM ZONE:</b>  | Zone 1, 2, 3                                     |
| <b>RECESS DEPTH:</b>             | Not Applicable                   | <b>VOLTAGE:</b>        | Mains 230V                                       |
| <b>FIRE RATING:</b>              | Not Applicable                   | <b>PRODUCT F MARK:</b> | Not suitable for mounting on flammable materials |

### LAMP

|                             |                |                                   |               |
|-----------------------------|----------------|-----------------------------------|---------------|
| <b>LIGHT SOURCE:</b>        | LED Module     | <b>MACADAM ELLIPSE:</b>           | 3-Step        |
| <b>MAXIMUM WATTAGE:</b>     | 8.1W           | <b>UGR:</b>                       | To Be Advised |
| <b>MAXIMUM LAMP LENGTH:</b> | Not Applicable | <b>BEAM ANGLE:</b>                | 35 (Degrees)  |
| <b>LAMP INCLUDED?</b>       | Yes (Integral) | <b>TILT ADJUSTMENT ANGLE:</b>     | 90 (Degrees)  |
| <b>LUMINOUS FLUX:</b>       | 490 (lm)       | <b>ROTATION ADJUSTMENT ANGLE:</b> | 330 (Degrees) |
| <b>COLOUR TEMP:</b>         | 3000 (K)       | <b>AVERAGE LIFESPAN:</b>          | 40,000 (Hrs)  |
| <b>CRI:</b>                 | 80             | <b>L70:</b>                       | To Be Advised |
| <b>R9:</b>                  | 1.5            |                                   |               |


### ELECTRICAL

|                               |                                 |                                 |                |
|-------------------------------|---------------------------------|---------------------------------|----------------|
| <b>SWITCHED:</b>              | No                              | <b>SUPPLY FREQUENCY:</b>        | 50/60 (Hz)     |
| <b>DIMMABLE:</b>              | Yes                             | <b>DRIVER/BALLAST VOLTAGE:</b>  | 210-250 (V)    |
| <b>DIMMING METHOD:</b>        | Phase - Leading & Trailing Edge | <b>DRIVER AVERAGE LIFESPAN:</b> | 40,000 (Hrs)   |
| <b>DRIVER OUTPUT CURRENT:</b> | Not Applicable                  | <b>EFFICACY:</b>                | 60.5 (lm/W)    |
| <b>DRIVER OUTPUT VOLTAGE:</b> | Not Applicable                  | <b>DRIVER/BALLAST INCLUDED?</b> | Yes (Integral) |

## ADDITIONAL INFORMATION

### ONEROUS ENVIRONMENTS

All of our exterior products are covered by a 3 year guarantee; however this does not apply to any that are installed within 5 miles of the coast. For these environments, please filter products on the Astro website by "Coastal".



BOX QUANTITY x 20



## PRODUCT ELEVATIONS

**GB** Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

**FR** Veuillez noter que certaines dimensions peuvent varier légèrement en raison des tolérances de fabrication, y compris l'entrée de câble et les trous de fixation.

**DE** Bitte beachten Sie, dass die Maße Fertigungstoleranzen unterliegen und daher in geringem Umfang von der angegebenen Größe abweichen können. Dies gilt auch für Kabeleingänge und Befestigungslöcher.

**IT** Si prega notare che possono esserci piccole variazioni in alcune dimensioni dovute alle tolleranze di produzione, queste includono l'ingresso del cavo e i fori di fissaggio.

